



ICAR-INDIAN GRASSLAND AND FODDER RESEARCH INSTITUTE

भा.कृ.अनु.प.-भारतीय चरागाह एवं चारा अनुसंधान संस्थान

JHANSI – 284 003 (U.P.)

झाँसी – 284 003 (उ.प्र.)



Phone No. 0510-2730908 e-mail: director.igfri@icar.gov.in, igfri.director@gmail.com

F.No.Estate/Construction of Tem. Shed/Store RRS Palampur/2022-23 Dated: 18.01.23

CORRIGENDUM

Sub.: Construction of Temporary Shed/Store, IGFRI-Himachal Pasturelands Palampur, Himachal Pradesh – reg.

Ref.: E-tender (Tender Id: 2023_DARE_734453_1).

With reference to the e-tender (Tender Id: 2023_DARE_734453_1) of this institute's published in the CPP portal, following corrigendum in the column of "Description of Work" of two items of the BOQ/Financial Bid sheet has been made:

S.No. of item mentioned in BOQ	FOR	READ AS
8.01	Providing and fixing precoated galvanized iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+0.05%) total coated thickness with zinc coating 120 grams per sqm as per IS:277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyster top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length up to 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling/self tapping screws of size (5.5x55 mm) with EPDM seal, complete up to any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	Providing and fixing 1mm thick M.S. sheet door with frame of 40x40x6 mm angle iron and 3 mm M.S. gusset plates at the junctions and corners, all necessary fittings complete, including applying a priming coat of approved steel primer. Using M.S. angels 40x40x6 mm for diagonol braces

13.01	<p>Providing reinforced by organic fibres and/or inorganic synthetic fibres cement 6 mm thick corrugated sheets (as per IS: 14871) roofing up to any pitch and fixing with polymer coated J, or L hooks, bolts and nuts 8 mm dia. G.I. plain and bitumen washers or with self drilling fastener and EPDM washers etc. complete (excluding the cost of purlins, rafters and trusses), including cutting sheets to size and shape wherever required.</p>	<p>Providing and fixing precoated galvanized iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+0.05%) total coated thickness with zinc coating 120 grams per sqm as per IS:277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyster top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length up to 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling/self tapping screws of size (5.5x55 mm) with EPDM seal, complete up to any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.</p>
-------	--	---

The other contents of the tender document remain unchanged.

Sd/-
Asstt. Admin. Officer (Store-Purchase)